



## **TECHNICAL SPECIFICATIONS**

### **CABALLERO 500 DELUXE**

**Homologation:** Euro5

**Engine:** Single cylinder 4 stroke, liquid cooled

**Displacement:** 449 cc

**Max Power detected\*:** 40 Hp @ 7500 rpm

**Max Torque detected\*:** 43 Nm @ 6000 rpm

**Bore:** 94.5 mm

**Stroke:** 64 mm

**Distribution:** Single camshaft - 4 valve

**Fuel system:** Electronic Fuel injection by ATHENA GET - throttle body  $\varnothing$  40mm

**Starter:** Electric

**Gears:** 6

**Clutch:** Multi plate wet clutch

**Exhaust system:** Dual exhaust by ARROW

**Frame:** CrMo steel central-tube frame

**Swingarm:** In steel with variable section and progressive link

**Tires:** 110/80 R19, 140/80 R17

**Wheels:** Spoked with aluminum rims

**Brakes:** Front floating brake disc  $\varnothing$ 320mm – Rear brake disc  $\varnothing$ 230mm

**ABS:** Continental two-channel ABS (disengageable)

**Front suspension:** FANTIC FRS  $\varnothing$ 41mm upside down

**Front suspension travel:** 150mm

**Rear suspension:** FANTIC FRS, rebound damping regulation

**Rear suspension travel:** 150mm

**Seat height:** 820 mm – optional seat 840mm

**Wheelbase:** 1425 mm

**Length:** 2080 mm

**Dry weight:** 150 kg

**Fuel Tank:** 12 l

**Fuel consumption:** 4,2 l/100 km

**CO2 emission:** 97 g/km

\* Data from the manufacturer. The measured values may differ slightly depending on the type of instrumentation used and environmental conditions present at the time of measurement.

